

# SAFETY DATA SHEET: SD/P01

in accordance with directives 91/155/EEC, and § 14 - GefStoffV. (ordinance on hazardous substances) revised on 18.12.2003

## 1. Identification of the substance / preparation and of the company

### Product details:

The safety data sheet is valid for the following products:

Trade names:	
<b>MARMORIT FAP 263®</b>	Fibrous plaster
<b>MARMORIT MM 215®</b>	Masonry mortar
<b>MARMORIT UP 210</b>	Lime-and-cement basecoat render

### Manufacturer / supplier identification

Manufacturer/Supplier:	KNAUF MARMORIT GmbH
Street/P.O. box:	Ellighofen 6
Nat. Ident./Postal code/City:	D-79283 Bollschweil
Telephone:	(0 76 33) 8 10-0
Facsimile:	(0 76 33) 8 10-113
Department responsible for information:	Qualitätswesen (Quality Department)
Telephone:	(0 76 33) 8 10-142
Emergency information:	Beratungsstelle für Vergiftungserscheinungen und Embryonaltoxikologie, Berlin
Emergency telephone number:	(0 30) 1 92 40

## 2. Composition / Information on ingredients

Description: Dry mortar, according to DIN 18557 composed of mineral bonding material and aggregates.

Substances with identification requirement:

CAS No.:	1305-62-0
Designation:	calcium hydroxide
Index:	Xi
Risk phrases:	R 36, 38
M %:	0 - 5 %

CAS No.:	68475-76-3
Designation:	Portland cement
Index:	Xi
Risk phrases:	R 38, 41, 43
M %:	5 - 10%

Identification numbers:  
215-137-3 (Einecs No.) for calcium hydroxide  
266-043-4 (Einecs No.) for Portland cement

### Additional information:

The hazard designation „irritating“ is not applicable for dry powder, but only after moisture or water action (alkaline reaction).  
The preparation is low in chromate in accordance with TRGS 613.

## 3. Hazard Identification

Hazard identification:  
Xi, irritant

Information pertaining to particular dangers for man:  
R 36 Irritant to the eyes.  
R 43 May cause sensitization by skin contact

## 4. First Aid Measures

General information:  
S 2 Keep out of reach of children

After inhalation:  
S 22 Do not inhale the dust

After skin contact:  
S 24 Avoid any contact with the skin

After eye contact:  
S26 Immediately rinse opened eye thoroughly under running water and seek medical advice.

After ingestion:  
S46 In case of ingestion seek medical attention immediately and show packaging or label.

## 5. Fire Fighting Measures

Suitable extinguishing media:  
Mortar is non flammable; for larger ambient fires use powder type fire extinguisher

## 6. Accidental Release Measures

Person-related safety precautions:  
Not applicable.

Measures for environmental protection:  
Do not allow to enter sewers and drains uncontrolled

Measures for cleaning/collecting:  
Pick up mechanically (dry).

## 7. Handling and Storage

### Handling

Information for safe handling:  
Transport in closed receptacles or packaging.

### Storage

Requirements to be met by storerooms and receptacles:  
Keep away from moisture. Store under dry conditions.

# SAFETY DATA SHEET: SD/P01

in accordance with directives 91/155/EEC, and § 14 - GefStoffV. (ordinance on hazardous substances) revised on 18.12.2003

## 8. Exposure Controls and Personal Protection

Components with workplace relevant concentration limits that require monitoring at the workplace.

CAS No.: 68475-76-3  
Designation of material: Portland cement  
Type: MAK  
Value: 5  
Unit: mg/m<sup>3</sup>

The indicated value has been taken from the lists valid at the time of issue (e. g. TRGS 900 for the Federal Republic of Germany).

### Personal protective equipment

Respiratory protection:  
Wear breathing mask in case of formation of dust.

Hand protection / eye protection:  
S37/S39 Wear appropriate protective gloves and safety glasses / face screen

Body protection: Not applicable

Hygienic measures:  
Observe the regulations of the respective trade association.  
(Instructions ZH 1 / 134 Hauptverband d. Gewerbl. BG).

## 9. Physical and Chemical Properties

### Appearance

Form: powder  
Color: gray-beige  
Odor: odorless

Apparent density (T=20°C) 0.9 - 1.5 g/cm<sup>3</sup>  
pH value (T=20°C) 11.5 - 13.0  
Solubility (in water) (T=20°C) 1,650 mg/l  
(for calcium hydroxide)

## 10. Stability and Reactivity

Materials to be avoided: not applicable

## 11. Toxicological Information

None

## 12. Ecological Information

Ecotoxicological effects:  
Do not allow mortar to reach inshore waters / ground water, water course or sewage system uncontrolled; disturbance caused by increased pH value.

## 13. Disposal Considerations

### Product

EAK-Code:  
17 09 04 Mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03.

Recommendation:  
Can be reused if picked up dry. Let residues with water become hardened and dispose of these rests on the disposal site for construction waste.

## 14. Transport Information

Comments:  
No identification required.

## 15. Regulatory Information

### Identification in accordance with the EC directives

Code letter and hazard designation of the product:  
Xi irritant

### Risk phrases:

R 36 Irritant to the eyes  
R 43 May cause sensitization by skin contact.

### Safety phrases:

S2 Keep out of reach of children  
S22 Do not inhale the dust  
S24 Avoid any contact with the skin  
S26 After eye contact: Immediately rinse opened eye thoroughly under running water and seek medical advice.  
S37/39 Wear suitable protective gloves and eye/face protection.  
S46 In case of ingestion seek medical attention immediately and show packaging or label.

### National Regulations

Water risk class:  
1 (self assessment)

## 16. Other Information:

Department that issues the data sheet:  
Quality management department

Contact: Dr. Sigmund